

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bergolin Härter EP 05 7E569

Product group: Produkt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener for 2K epoxy resin systems

1.3. Details of the supplier of the safety data sheet

Company name: Tenax Marine Paints Vertriebs GmbH
Street: Sachsenring 1
Place: D-27711 Osterholz-Scharmbeck
Telephone: 04795-95899 0
e-mail: info@tmp-coatings.de
Contact person: Sicherheitsdatenblattverwaltung
e-mail: sdb@bergolin.de
Internet: www.tmp-coatings.de

1.4. Emergency telephone number: 04795-95899-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
Acute Tox. 4; H312
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

reaction mass of ethylbenzene and xylene

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312+H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 2 of 13

H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use ... to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH208	Contains Amines, polyethylenepoly-, triethylenetetramine fraction. May produce an allergic reaction.
--------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polyamine system

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	reaction mass of ethylbenzene and xylene			55 - < 60 %
	905-588-0		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine			30 - < 35 %
	Eye Dam. 1; H318			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			10 - < 15 %
	203-539-1	603-064-00-3	01-2119457435-35	
	Flam. Liq. 3, STOT SE 3; H226 H336			
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction			< 1 %
	292-588-2		01-2119487919-13	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 3 of 13

Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/?.
Do not wash with: Solvent/Thinner.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam. Carbon dioxide. Powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Do not allow water used to extinguish fire to enter drains or waterways.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed containers for disposal.

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 4 of 13

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Disposal: see section 13

SECTION 7: Handling and storage

Personal protection equipment: see section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid release to the environment. In use, may form flammable/explosive vapour-air mixture.

Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools.

Wear antistatic work clothing.

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. When using do not eat, drink or smoke. Wear personal protection equipment.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Hints on joint storage**

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	
		150	568		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 5 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	reaction mass of ethylbenzene and xylene			
Consumer DNEL, long-term		inhalation	local	65,3 mg/m³
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m³
Consumer DNEL, acute		inhalation	systemic	260 mg/m³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	5 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	221 mg/m³
Worker DNEL, long-term		inhalation	systemic	221 mg/m³
Worker DNEL, acute		inhalation	local	442 mg/m³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	442 mg/m³
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			
Worker DNEL, acute		inhalation	local	553,5 mg/m³
Worker DNEL, long-term		dermal	systemic	50,6 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	369 mg/m³
Consumer DNEL, long-term		dermal	systemic	18,1 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	43,9 mg/m³
Consumer DNEL, long-term		oral	systemic	3,3 mg/kg bw/day
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction			
Worker DNEL, long-term		dermal	local	0,028 mg/cm²
Worker DNEL, long-term		inhalation	systemic	1 mg/m³
Worker DNEL, acute		inhalation	systemic	5380 mg/m³
Worker DNEL, long-term		dermal	systemic	0,57 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,29 mg/m³
Consumer DNEL, acute		inhalation	systemic	1600 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
	reaction mass of ethylbenzene and xylene	
	Freshwater	0,044 mg/l
	Freshwater (intermittent releases)	0,01 mg/l
	Marine water	0,004 mg/l
	Freshwater sediment	2,52 mg/kg
	Marine sediment	0,252 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1,6 mg/l
	Soil	0,852 mg/kg
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	
	Freshwater	10 mg/l
	Freshwater (intermittent releases)	100 mg/l
	Marine water	1 mg/l
	Freshwater sediment	41,6 mg/kg
	Marine sediment	4,17 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	2,47 mg/kg
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	
	Freshwater	0,190 mg/l
	Marine water	0,038 mg/l
	Freshwater sediment	95,9 mg/kg
	Marine sediment	19,2 mg/kg
	Soil	19,1 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: butyl rubber or Viton (necessarily consider the permanence of the material and See information supplied by the manufacturer.)

Breakthrough time (maximum wearing time): ____ min.

Use protective skin cream before handling the product.

Skin protection

Wear antistatic work clothing. (Natural fibres (e.g. cotton)/ heat-resistant synthetic fibres)

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 7 of 13

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

Test method

Changes in the physical state

Boiling point or initial boiling point and boiling range:	119 °C
Flash point:	25 °C DIN 53213
Lower explosion limits:	1 vol. %
Upper explosion limits:	13,1 vol. %
Auto-ignition temperature:	290 °C
Vapour pressure: (at 20 °C)	13,3 hPa
Vapour pressure: (at 50 °C)	45 hPa
Density (at 20 °C):	0,91 g/cm ³ DIN 53217
Flow time: (at 20 °C)	10 6 DIN EN ISO 2431
Solvent separation test:	<3 % (ADR/RID)
Solvent content:	69,00 %

9.2. Other information

Solid content:	31,00 %
----------------	---------

SECTION 10: Stability and reactivity

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

10.4. Conditions to avoid

In case of warming: Thermal decomposition.

10.6. Hazardous decomposition products

Carbon monoxide Carbon dioxide. Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful in contact with skin.

Harmful if inhaled.

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 8 of 13

ATEmix calculated

ATE (dermal) 1964,3 mg/kg; ATE (inhalation vapour) 19,64 mg/l; ATE (inhalation dust/mist) 2,679 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	reaction mass of ethylbenzene and xylene				
	oral	LD50 >2000 mg/kg			
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 5200 mg/kg	Ratte		
	dermal	LD50 14000 mg/kg	Kaninchen		
	inhalation (4 h) vapour	LC50 54,6 mg/l	Ratte		
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction				
	oral	LD50 1716 mg/kg	Rat		
	dermal	LD50 1465 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Contains Amines, polyethylenepoly-, triethylenetetramine fraction. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (reaction mass of ethylbenzene and xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (reaction mass of ethylbenzene and xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience

Observations relevant to classification

Following inhalation:

May cause respiratory irritation. Potential hazards: Liver and kidney damage. Depression of the central nervous system. Symptoms: Headache. Dizziness. Causes drowsiness or dizziness. unconsciousness.

After skin contact:

The product is skin resorptive. Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 9 of 13

Following eye contact:
Irritating to eyes. (reversible.)

after ingestion:
Nausea. vomiting. gastro-intestinal ailment.

Further information

There are no data available on the preparation/mixture itself.
The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	reaction mass of ethylbenzene and xylene					
	Acute fish toxicity	LC50 2,6 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout) Ceriodaphnia spec		
	Acute algae toxicity	ErC50 4,7 mg/l	72 h	Selenastrum capricornutum		
	Crustacea toxicity	NOEC 0,44 mg/l	21 d	Pseudokirchneriella subcapitata		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 >4600 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 >1000 mg/l	96 h			
	Acute crustacea toxicity	EC50 23300 mg/l	48 h	Daphnia magna		
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction					
	Acute fish toxicity	LC50 330 mg/l	96 h	Pimephales promelas		

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			
	OECD 301E	96%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	reaction mass of ethylbenzene and xylene	3,16
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	0,37

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 10 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
	reaction mass of ethylbenzene and xylene	25,9		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	<100		

Further information

There are no data available on the preparation/mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.
Remove according to the regulations.

List of Wastes Code - residues/unused products

160508 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; discarded organic chemicals consisting of or containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.
Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Revision date: 02.06.2026

Bergolin Härter EP 05 7E569

Page 11 of 13



Special Provisions: 163, 223, 367, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3 A72 A192
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 69 % (627,9 g/l)
2004/42/EC (VOC): 69 % (627,9 g/l)
Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2, 15.

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 12 of 13

Abbreviations and acronyms

ADR - Accord européen relatif transport des marchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - „Derived No-Effect Level“; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Amines, polyethylenepoly-, triethylenetetramine fraction. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

TMP

according to Regulation (EC) No 1907/2006

Bergolin Härter EP 05 7E569

Revision date: 02.06.2026

Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)