according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Dura-Plate® Poxicolor SW N Comp. B

Product code : 0000000000559801

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub: Coatings and paints, thinners, paint removers

stance/Mixture

Recommended restrictions :

on use

Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Sherwin-Williams Coatings

Deutschland GmbH

Rieter Tal 1

71665 Vaihingen / Enz

Telephone : +4970421090

E-mail address of person

responsible for the SDS

: SDS-DE@sherwin.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number: Not available

Supplier

Telephone number: +49 (0) 7042 109-0

Hours of operation: Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Sub-category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Short-term (acute) aquatic hazard, Cate- H400: Very toxic to aquatic life.

1 / 18

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

gory 1

Long-term (chronic) aquatic hazard, Cat-

H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH071

Corrosive to the respiratory tract.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P391 Collect spillage.

Hazardous components which must be listed on the label:

Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated

1,3-Cyclohexanedimethanamine

Cashew, nutshell liq.

m-phenylenebis(methylamine)

Phenolformaldehyd resin

3-aminopropyldiethylamine

trimethylhexane-1.6-diamine

1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Carbomonocyclic alkylated mix-	1173092-74-4	Acute Tox. 4; H302	>= 25 - < 30
tures of poly-aza-alcanes, hydro-		Skin Corr. 1C; H314	
genated		Eye Dam. 1; H318	
		Skin Sens. 1A; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2; H411	
1,3-Cyclohexanedimethanamine	2579-20-6	Acute Tox. 4; H302	>= 10 - < 20
1,3-Cyclonexanedimethanamine	219-941-5	Acute Tox. 4, 11302 Acute Tox. 4; H312	<i>y</i> = 10 - < 20
	01-2119543741-41-	Skin Corr. 1A; H314	
	XXXX	Eye Dam. 1; H318	
	7.0.0.0	Aquatic Chronic 3;	
		H412	
Polyoxypropylenediamine (poly-	9046-10-0	Acute Tox. 4; H302	>= 10 - < 20
mer)		Acute Tox. 4; H312	
		Skin Corr. 1B; H314	
		Aquatic Chronic 3;	
		H412	
		Eye Dam. 1; H318	
Cashew, nutshell liq.	8007-24-7	Acute Tox. 4; H302	>= 3 - < 10
	232-355-4	Acute Tox. 4; H312	
	01-2119502450-57-	Skin Irrit. 2; H315	
	XXXX	Eye Dam. 1; H318	
m nhandanahia/mathdamina)	1477-55-0	Skin Sens. 1A; H317	>= 5 - < 10
m-phenylenebis(methylamine)	216-032-5	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 5 - < 10
	01-2119480150-50-	Skin Corr. 1B; H314	
	XXXX	Skin Con. 1B, 11314 Skin Sens. 1; H317	
	7000	Aquatic Chronic 3;	
		H412	
	3 / 18		

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

		EUH071	
Phenolformaldehyd resin	9003-35-4 500-005-2 01-2120735197-51- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 10
3-aminopropyldiethylamine	104-78-9 203-236-4 612-062-00-1 01-2119965402-39- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 3 - < 5
trimethylhexane-1,6-diamine	25620-58-0 247-134-8 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412	>= 2,5 - < 3
1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.	404362-22-7 445-790-1 01-0000018826-60- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1A; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with difficul-

ty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : There are no data available on the mixture itself. Procedure

used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inha-

lation and dermal routes of exposure and eye contact.

Risks : Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Good housekeeping standards, regular safe removal of waste

materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire

hazards.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

used.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must

comply with the technological safety standards.

Storage class (TRGS 510) : 8A

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Phenolformalde-	9003-35-4	AGW (Inhalable	10 mg/m3	DE TRGS
hyd resin		fraction)		900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)		900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			

8.2 Exposure controls

Personal protective equipment

Eye protection : Equipment should conform to EN 166

Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version **Revision Date:** Date of last issue: -

Date of first issue: 15.12.2022 1.0 15.12.2022

Glove length Standard glove type.

Directive Equipment should conform to EN 374

Material Protective equipment only chosen according to specific regu-

latory requirements after a risk assessment.

Material Chemical resistant gloves made of butyl rubber or nitrile rub-

ber category III according to EN 374.

Remarks Follow the instructions for use issued by the producer.

> Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection Rubber apron

Boots

Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection Equipment should conform to EN 14387

> General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

In case of insufficient ventilation, wear suitable respiratory Protective measures

equipment.

Environmental exposure controls

Water

The product should not be allowed to enter drains, water

courses or the soil.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : red

Odour : amine-like

Odour Threshold : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : > 101 °C

Method: closed cup

Auto-ignition temperature : Not relevant/applicable due to the nature of the product.

Decomposition temperature : Not relevant/applicable due to the nature of the product.

pH : Not relevant/applicable due to the nature of the product.

Viscosity

Viscosity, dynamic : ca. 270 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not relevant/applicable due to the nature of the product.

Vapour pressure : 0,34 hPa

Density : ca. 0,99 g/cm3 (20 °C)

Relative vapour density : Not relevant/applicable due to the nature of the product.

9.2 Other information

Explosives : No dangerous reaction known under conditions of normal use.

Oxidizing properties : No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of :

exposure

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 819,17 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

1,3-Cyclohexanedimethanamine:

Acute oral toxicity : LD50 Oral (Rat): 780 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1.700 mg/kg

Cashew, nutshell liq.:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2.000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

3-aminopropyldiethylamine:

Acute oral toxicity : LD50 Oral (Rat): 1.410 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 524 mg/kg

1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:

Acute oral toxicity : LD50 Oral (Rat): 1.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version **Revision Date:** Date of last issue: -

Date of first issue: 15.12.2022 1.0 15.12.2022

SECTION 12: Ecological information

12.1 Toxicity

Components:

m-phenylenebis(methylamine):

Toxicity to fish LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): 4 mg/l

NOEC: 0,14 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Exposure time: 21 d

ic toxicity) Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-The product should not be allowed to enter drains, water

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

mation courses or the soil.

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1760 IMDG : UN 1760 IATA : UN 1760

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, N.O.S.

(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,

hydrogenated, Polyoxypropylenediamine (polymer))

IMDG : CORROSIVE LIQUID, N.O.S.

(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,

hydrogenated, Polyoxypropylenediamine (polymer))

IATA : Corrosive liquid, n.o.s.

(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,

hydrogenated, Polyoxypropylenediamine (polymer))

14.3 Transport hazard class(es)

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

Packing group : II Classification Code : C9

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Date of last issue: -Version Revision Date:

Date of first issue: 15.12.2022 1.0 15.12.2022

Hazard Identification Number : 80 Labels 8 Tunnel restriction code (E)

IMDG

Packing group Ш Labels 8 **EmS Code** F-A, S-B

IATA (Cargo)

Packing instruction (cargo 855

aircraft)

Packing instruction (LQ) Y840 Packing group Ш Labels Corrosive

IATA (Passenger)

Packing instruction (passen-851

ger aircraft)

Packing instruction (LQ) Y840 Packing group Ш

Labels Corrosive

14.5 Environmental hazards

Environmentally hazardous yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the Euro- E1 ENVIRONMENTAL HAZARDS

pean Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Water hazard class (Germa: WGK 3 highly hazardous to water

ny) Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:

Not applicable

Inorganic substances in powdered form:

Not applicable

Inorganic substances in vapour or gaseous form:

: Not applicable

Not applicable
Organic Substances:
Not applicable

Carcinogenic substances:

Not applicable Mutagenic: Not applicable Toxic to reproduction:

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

15.2 Chemical safety assessment

This product is in full compliance according to REACH regulation 1907/2006/EC. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

H332 : Harmful if inhaled.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

H400 : Very toxic to aquatic life.

H410
H411
Toxic to aquatic life with long lasting effects.
H412
Harmful to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA

according to Regulation (EC) No. 1907/2006

Dura-Plate® Poxicolor SW N Comp. B

Version Revision Date: Date of last issue: -

1.0 15.12.2022 Date of first issue: 15.12.2022

- Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Corr. 1A	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

DE / EN